## création baumann

### **SHELTER**

Glare and heat protection; Aluminium vapour coated sheer in basket weave. The flame-retardant fabric with its look of filigree screen wards off intrusive stares and glare and provides protection at the window against ingress of heat and UV rays. It is equally well suited for applications in the contract sector as for residential furnishing. The curtain fabric unites functionality with innovation. The understated and comfortable surface bestows comfort and elegance to an interior.













Use: Glare & heat protection

Number of colours:

Special colours: - from 300 m / 330 yds without surcharge.

Material: 100% Flameretardant polyester

Fabric width: 300 cm/118 inch/3.28 yard

Can be railroaded: Can be railroaded

Weight: 246 g/m<sup>2</sup>

Flame-retardant properties:

Care:

Additional use:









Dry cleaning (length shrinkage): 1%

Alpha value 0.25 Sound absorption:

Light fastness: see downloads

Certificates / tests: Fire Test SNV 198898 Fire Test M1 \*all testing reports can be Fire Test NFPA 701 downloaded from our website

Light transmission DIN EN 410 under product details Lightfastness certificate

Sound absorption ISO 354 / ISO 11654

Special notes

Transmission values in overview

- The aluminium vapour coated reverse in a Special notes:

width of 300 cm is a real speciality.

- Col 109 is not certifyed by Oeko-Tex.

# création baumann

## **SHELTER**



### SYMBOLS AND PRODUCT INFORMATION

Product information		Material information
Inherently flame retardant	Free from harmful substances / Oddy	AC Acetate
		CA Hemp
Width (cm)	Antimicrobial (counteracts colonisation and multiplying of micro organisms and odours.)	CO Cotton
		<b>EA</b> Elasthan
Can be railroaded (only valid for curtains)	⇒ light transmission level Tv, n-h	GL Glass fibre
Has to be railroaded	light transmission level Tv. n-nn	LI Linen
		MD Modal
Must not be railroaded	⇒ k light transmission level Tv, n-dif	ME Metal
		PA Polyamide
Repeat in warp direction	light reflection level Pv, n-h	PC Acrylic
		PE Polyethylene
Repeat in weft direction	light absorption level Av	PI Paper
Weight (g/m2)	UV transmission level Tuv	PL Polyester
		PLF Flameretardant polyester
Yarn dyed	solar transmission level Te, n-h	PLF CS Flameretardant polyester (Trevira CS)
		PN Polycarbonat
Piece dyed	solar reflection level Pe, n-h	PP Polypropylene
		PU Polyurethan
Knitted	solar absorption level Ae	RA Ramie
		SE Silk
Woven	Usable in a bathroom/wet room (Plissee)	SI Silicone
		TR Different material (wood, paper, feathers etc.)
Warp print	Stain resistant (Plissee)	VI Viscose
Screen print/burnout	Various articles are only available in complete picture repeats.  The price is quoted per repeat in each case.	WM Wool Mohair
		wv Wool
Metalized on one side	Additional product information	
Pearl reflex		

### SYMBOLS AND PRODUCT INFORMATION

### Intended purposes 44 Curtains/Sheers Roller blinds (colours see separate roller blind collection) Panels (process the panels in warp direction to get optimal hang properties) Vertical blinds Roman blinds Upholstery (for heavy use in contract application). Martindale > 30'000 Upholstery (for heavy use in domestic application/for normal use in contract application). 20'000 < Martindale < 30'000 Upholstery (for normal use in domestic application/for careful use in contract application). Martindale < 20'000Loose cover for careful use in domestic application. Martindale < 5'000 **Bedspreads** Table cloth domestic use Wallcovering Textile wallpaper (can be paper backed, minimum quantity) Cushion Acoustical fabrics Adhesive Textiles/Gecko/Gecko in the Box

Fabrics with very high lightfastness for indoor and outdoor	use
Blackout BO	
Reverso	
Plisseé	
Comb plisseé	